

DAC 3000.3 FVZ / DAC 3000.4 VAC-P

Hauschild Engineering pioneered dual asymmetric centrifugal technology 50 years ago. Since then, Hauschild SpeedMixer® bladeless lab mixers have become a staple in R&D labs and production facilities around the world. Other companies manufacture or distribute bladeless mixers, but nothing compares to the quality, accuracy and reliability of a Hauschild SpeedMixer®. It's an investment that pays off at every turn.



Technical Data

Specification	DAC 3000.3 FVZ	DAC 3000.4 VAC-P
Mixing capacity (g/lb.)	Up to 3000 / 6,61 ¹	Up to 3000 / 6,61 ¹
Mixing volume (ml/gal)	Up to 6000 / 1,58	Up to 6000 / 1,58
Mixing Speed (rpm)	50 ÷ 1000	50 ÷ 900
Mixing time (min.)	10	10
Display	10" Color touchscreen	10" Color touchscreen
Internal light	Yes	Yes
Programs	300	300
Mixing steps/program	6	6
Vacuum	No	Yes
Minimum pressure (mbar)	N.A.	0
Vacuum pump	N.A.	External
Voltage - Frequency	380 - 500 V - 50/60 Hz	380 - 500 V - 50/60 Hz
Input Power KW	5,5	5,5
Hight Open lid (mm/inches)	1700 / 66,9	1700 / 66,9
Hight - Closed lid (mm/ inches)	1220 / 48	1220 / 48
Width (mm/ inches)	1710 / 67,3	1710 / 67,3
Depth (mm/ inches)	1200 / 47,2	1200 / 47,2
Weight (kg/lb.)	1200 / 2645	1250 / 2755

¹ Including material, jar, and holder when applicable.


Hauschild GmbH & Co. KG

Waterkamp 1

59075 Hamm, Germany

+49-2381-482050

info@hauschild-speedmixer.com



Hauschild SpeedMixer Inc.

37735 Enterprise Ct - Suite 300

Farmington Hills, MI 48331

+1-877-SPDMXER

info.us@hauschild-speedmixer.com

DAC 3000.3 FVZ / DAC 3000.4 VAC-P

Hauschild Engineering ist seit 50 Jahren Vorreiter bei der Technologie der Dualen Asymmetrischen Zentrifugaltechnologie. Seitdem sind die rührwerklosen Hauschild SpeedMixer® ein fester Bestandteil in Forschungs- und Entwicklungslaboren sowie Produktionsstätten auf der ganzen Welt. Andere Unternehmen stellen rührwerklose Mischer her oder vertreiben sie, aber nichts ist mit der Qualität, Genauigkeit und Zuverlässigkeit eines Hauschild SpeedMixer® vergleichbar. Es ist eine Investition, die sich in jeder Hinsicht auszahlt.




Technische Daten

Spezifikation	DAC 3000.3 FVZ	DAC 3000.4 VAC-P
Mischkapazität (g/lb.)	Bis 3000 / 6,61 ¹	Bis 3000 / 6,61 ¹
Mischvolumen (ml/gal)	Bis 6000 / 1,58	Bis 6000 / 1,58
Drehzahl (rpm)	50 ÷ 1000	50 ÷ 900
Max. Mischzeit (min)	10	10
Display	10" Color touchscreen	10" Color touchscreen
Internes Licht	Yes	Yes
Programmierbar	300	300
Mischschritte / Programm	6	6
Vakuum	No	Yes
Mindestdruck (mbar)	N.A.	0
Vakuum Pumpe	N.A.	External
Netzspannung - Frequenz	380 - 500 V - 50/60 Hz	380 - 500 V - 50/60 Hz
Nennleistung (kW)	5,5	5,5
Deckel offen - Höhe (mm/inches)	1700 / 66,9	1700 / 66,9
Deckel zu - Höhe (mm/ inches)	1220 / 48	1220 / 48
Breite (mm/ inches)	1710 / 67,3	1710 / 67,3
Tiefe (mm/ inches)	1200 / 47,2	1200 / 47,2
Gewicht (kg/lb.)	1200 / 2645	1250 / 2755

¹ Einschließlich Material, Gefäß und Halter, sofern zutreffend.

Hauschild GmbH & Co. KG

Waterkamp 1
59075 Hamm, Germany
+49-2381-482050
info@hauschild-speedmixer.com



Hauschild SpeedMixer Inc.

37735 Enterprise Ct - Suit 300
Farmington Hills, MI 48331
+1-877-SPDMXER
info.us@hauschild-speedmixer.com