

SMART DAC 15000.5 FVZ / SMART DAC 15000.6 VAC-P

Optional Configurations

Real Time Temperature Measurement
Indipendet Variable Counterrotation
LabCatch ready




Technical Data

Specification	SMART DAC 15000.5 FVZ	SMART DAC 15000.6 VAC-P
Mixing capacity (g/lb.)	Up to 15000 / 33,06	Up to 15000 / 33,06
Mixing volume (ml/gal)	Up to 22000 / 5,81	Up to 22000 / 5,81
Mixing Speed (rpm)	50 ÷ 450	50 ÷ 450
Mixing time (min.)	10 min. (30 min. Pro Version)	10 min. (30 min. Pro Version)
Display	10" Color touchscreen	10" Color touchscreen
Internal light	Yes	Yes
Programs	300 (500 Pro Version)	300 (500 Pro Version)
Mixing steps/program	6 (12 Pro Version)	6 (12 Pro Version)
Vacuum	No	Yes
Minimum pressure (mbar)	N.A.	0
Vacuum pump	N.A.	External
Voltage - Frequency	400 / 50-60 and 480 / 50-60	400 / 50-60 and 480 / 50-60
Input Power KW	1,1	1,1
Height Open lid (mm/inches)	1255 / 49,4	1255 / 49,4
Height - Closed lid (mm/ inches)	1906 / 75	1906 / 75
Width (mm/ inches)	2440 / 96	2440 / 96
Depth (mm/ inches)	1352 / 53,2	1352 / 53,2
Weight (kg/lb.)	2100 / 4629	2200 / 4850

Hauschild GmbH & Co. KG

Waterkamp 1
59075 Hamm, Germany
+49-2381-482050
www.speedmixer.com
info@speedmixer.com



Hauschild SpeedMixer Inc.

37735 Enterprise Ct - Suite 300
Farmington Hills, MI 48331
+1-877-SPDMXER
info.us@speedmixer.com

SMART DAC Features


Common features

10 minutes mixing time
300 programs
6 mixing zones/program
Automatic strobe light

Up to 20 litres / 5,28 gal
Start from 50 rpm
Customizable display view
Multilanguage

Optional features

30 minutes mixing time
500 programs
12 mixing zones/program
Multiprogram: combine up to 3 programs and up to 36 mixing zones
Acceleration/deceleration individually adjustable for each mixing zone
QR code scanner for fast program upload
Real time temperature reading
Variable counterrotation: increase or decrease the counterrotation independently from the main rotation
Sensors integration (housing temperature and humidity, smoke, fire, dissolved gases, ...)
SW for remote control and display mirroring
IoT compatible




Special SpeedMixer

200+ custom models
Robotic version, both standard and vacuum
Double basket versions
External remote control box for energetic material
Large cartridge special models



Hauschild GmbH & Co. KG

Waterkamp 1
59075 Hamm, Germany
+49-2381-482050
www.speedmixer.com
info@speedmixer.com



Hauschild SpeedMixer Inc.

37735 Enterprise Ct - Suite 300
Farmington Hills, MI 48331
+1-877-SPDMXER
info.us@speedmixer.com

SMART DAC 15000.5 FVZ / SMART DAC 15000.6 VAC-P

Optionale Konfigurationen

Echtzeit-Temperaturmessung
Variable Gegenrotation
LabCatch ready




Technische Daten

Spezifikation	SMART DAC 15000.5 FVZ	SMART DAC 15000.6 VAC-P
Mischkapazität (g/lb.)	Bis 15000 / 33,06	Bis 15000 / 33,06
Mischvolumen (ml/gal)	Bis 22000 / 5,81	Bis 22000 / 5,81
Drehzahl (rpm)	50 ÷ 450	50 ÷ 450
Max. Mischzeit (min)	10 min. (30 min. Pro Version)	10 min. (30 min. Pro Version)
Display	10" Farb-Touchscreen	10" Farb-Touchscreen
Internes Licht	Ja	Ja
Programmierbar	300 (500 Pro Version)	300 (500 Pro Version)
Mischschritte / Programm	6 (12 Pro Version)	6 (12 Pro Version)
Vakuum	Nein	Ja
Mindestdruck (mbar)	N.A.	0
Vakuum Pumpe	N.A.	Externe
Netzspannung - Frequenz	400 / 50-60 and 480 / 50-60	400 / 50-60 and 480 / 50-60
Nennleistung (kW)	1,1	1,1
Deckel offen - Höhe (mm/inches)	1255 / 49,4	1255 / 49,4
Deckel zu - Höhe (mm/ inches)	1906 / 75	1906 / 75
Breite (mm/ inches)	2440 / 96	2440 / 96
Tiefe (mm/ inches)	1352 / 53,2	1352 / 53,2
Gewicht (kg/lb.)	2100 / 4629	2200 / 4850

Hauschild GmbH & Co. KG

Waterkamp 1
59075 Hamm, Germany
+49-2381-482050
www.speedmixer.com
info@speedmixer.com



Hauschild SpeedMixer Inc.

37735 Enterprise Ct - Suite 300
Farmington Hills, MI 48331
+1-877-SPDMXER
info.us@speedmixer.com

Gemeinsamkeiten

10 Minuten Mischzeit
300 Programme
6 Mischzonen/Programm
Automatisches Stroboskoplicht

Bis zu 20 Liter (5,28 gal) Behälter
Von 50 rpm
Anpassbare Anzeigeansicht
Mehrsprachig


Optionale Features

30 Minuten Mischzeit
500 Programme
12 Mischzonen/Programm
Multiprogramm: Kombinieren Sie bis zu 3 Programme und bis zu 36 Mischzonen
Beschleunigung/Verzögerung individuell einstellbar für jede Mischzone
QR code scanner für schnellen Programm-Upload
Temperaturmessung in Echtzeit
Variable Gegenrotation: Erhöhen oder verringern Sie die Gegenrotation
unabhängig von der Hauptrotation
Sensorintegration (Gehäusetemperatur und -feuchtigkeit, Rauch, Feuer, gelöste Gase, ...
SW für Fernsteuerung und Displayspiegelung
IoT-kompatibel




Sondermaschinen

Über 200 Sondermodelle
Roboterversion, sowohl Standard- als auch Vakuumversion
Doppel-MBA-versionen
Externe Fernbedienungsbox für energetisches Material
Große Kartuschen-Sondermodelle



Hauschild GmbH & Co. KG

Waterkamp 1
59075 Hamm, Germany
+49-2381-482050
www.speedmixer.com
info@speedmixer.com



Hauschild SpeedMixer Inc.

37735 Enterprise Ct - Suite 300
Farmington Hills, MI 48331
+1-877-SPDMXER
info.us@speedmixer.com